

Délky spirálových vrtáků

Průměr vrtáku		DIN 338		DIN 340		DIN 1897		DIN 1869 řada 1		DIN 1869 řada 2		DIN 1869 řada 3	
od	do	L	ld (min)	L	ld (min)	L	ld (min)	L	ld (min)	L	ld (min)	L	ld (min)
0,96	1,06	34	12	56	33	26	6						
1,07	1,18	36	14	60	37	28	7						
1,19	1,32	38	16	65	41	30	8						
1,33	1,50	40	18	70	45	32	9						
1,51	1,70	43	20	76	50	34	10						
1,71	1,90	46	22	80	53	36	11						
1,91	2,12	49	24	85	56	38	12	125	85				
2,13	2,36	53	27	90	59	40	13	135	90				
2,37	2,65	57	30	95	62	43	14	140	95				
2,66	3,00	61	33	100	66	46	16	150	100	190	130		
3,01	3,35	65	36	106	69	49	18	155	105	200	135		
3,36	3,75	70	39	112	73	52	20	165	115	210	145	265	180
3,76	4,25	75	43	119	78	55	22	175	120	220	150	280	190
4,26	4,75	80	47	126	82	58	24	185	125	235	160	295	200
4,76	5,30	86	52	132	87	62	26	195	135	245	170	315	210
5,31	6,00	93	57	139	91	66	28	205	140	260	180	330	225
6,01	6,70	101	63	148	97	70	31	215	150	275	190	350	235
6,71	7,50	109	69	156	102	74	34	225	155	290	200	370	250
7,51	8,50	117	75	165	109	79	37	240	165	305	210	390	265
8,51	9,50	125	81	175	115	84	40	250	175	320	220	410	280
9,51	10,60	133	87	184	121	89	43	265	185	340	235	430	295
10,61	11,80	142	94	195	128	95	47	280	195	365	250	455	310
11,81	13,20	151	101	205	134	102	51	295	205	375	260	480	330
13,21	14,00	160	108	214	140	107	54						
14,01	15,00	169	114	220	144	111	56						
15,01	16,00	178	120	227	149	115	58						
16,01	17,00	184	125			119	60						
17,01	18,00	191	130			123	62						
18,01	19,00	198	135			127	64						
19,01	20,00	205	140			131	66						

Délka		Tolerance	Tolerance
od	do	L	l
3	6	± 0,5	+ 1,0
7	30	± 1,0	+ 2,0
31	120	± 1,5	+ 3,0
121	400	± 2,0	+ 4,0
401	1000	± 3,0	+ 6,0

Všechny rozměry jsou v mm.